

USING THE PROPER STONE CARE PRODUCTS TO PROTECT STONE

ISHINOL SERIES
AQUA CLEAR
(for white granite)

- * Water type permeable inorganic agent
- * Prevents suction of water
- * Odorless
- * Does not contain solvent
- * No flammability.
- * Safe for storage



【CHARACTERISTICS】

1. Does not spoil the stone appearance. (Natural finish)
2. Penetrates into the stone and is excellent to the durability.
3. Is superior to prevent the suction of water.
4. Water type and is easy to use.
5. Does not spoil the stone ventilation.

【STANDARD APPLICATION QUANTITY】

White granite (Polished finish) ... 10 ~ 20 m²/L

White granite (Jet burnered finish) ... 6 ~ 10 m²/L

- ⇒ * It varies by the kind of stones.
* Before coating, test a small out of the way area. The color may change on some stone.

When uses AQUA CLEAR other than white granite, please ask to agent or maker

【PACKING】

10 liter carton box

KONSHO CO.,LTD.

【USAGE】

- * Before application, test on a sample piece of the stone.
 - * Wash thoroughly with ISHICLEAN Series removing all stains and wax.
 - * Allow thorough drying after washing. Otherwise, unevenness in color may occur.
 - * Equally apply undiluted AQUA CLEAR to the surface area with a towel, mop, roller, brush.
- <In case of polished stone>
- ↓ After 5 minutes, buff out remaining liquid on the surface with a dry towel.
Buffing is not necessary for jet-burner finish.
- * Allow to dry for about 24 hours. Be careful not to get the surface wet with water during the drying period.

【CHARACTERISTICS】

Appearance :	Clear colorless liquid
pH :	approx. 13
Specific gravity :	approx. 1.1

【NOTE】

- AQUA CLEAR is for only white granite. When uses AQUA CLEAR with other stones, please ask agent or maker.
 - Test samples before application.
- When a surface is hot with the direct sunlight etc., AQUA CLEAR may not penetrate and may be stiffened in the surface. It is the cause that white crystal will adhere to the surface.
- When applies AQUA CLEAR to the back side, adhesive strength decreases so recommend to use with Ishi Cement F together.
 - Be careful not to get the surface wet with water during the drying period.
 - Wash the tools with water immediate after use.
 - Buff out thoroughly for the polished surface within 5 minutes after coating.
 - Wear protective glove, an apron etc.
 - First aid treatment :
 - Skin contact ... Flush with water and soap
 - Eye contact ... Flush with water thoroughly and get medical attention.
 - Rinse mouth and wash hands after handling.
 - Wipe with a cloth etc. when spill out.
 - Store at cool and dark place. Do not store below 0°C.
 - Refer MSDS for other details.

KONSHO CO.,LTD.